



**FOREVER
FIREPLACE**

36" AND 42" WOOD BURNING FIREPLACES

HIGH QUALITY

All Stainless steel
construction built
in the USA.

HIGH HEAT

Fully Insulated firebox
and high-quality refractory
panels result in a superior
heat radiation.

HIGH VERSATILITY

Use as a replacement
appliance or for new
construction. Approved
to add vented and
vent free gas logs.



Manufactured by

LYMPIA
CHIMNEY & VENTING



**LOOK NO FURTHER! THE VENTIS®
FOREVER FIREPLACE IS THE ONLY
FIREPLACE YOU WILL EVER NEED.**

This is the latest in modern manufactured fireplace technology made right here in the USA. The **Forever Fireplace** features quality craftsmanship in an all stainless steel construction that's built to stand the test of time and bring warmth to your family for many years to come. With a sloped smoke chamber and fully insulated firebox, the **Forever Fireplace** efficiently adds radiant heat to the heart of your home. Don't want to burn wood? The **Forever Fireplace** is also approved to add vented or vent free gas logs. When you want the best in a durable fireplace that lasts a lifetime, look no further than the **VENTIS FOREVER FIREPLACE!**



High quality optional doors



COMPLETE STAINLESS STEEL CONSTRUCTION

- Competitor boxes use galvanized metals.
- 304 stainless steel grate is resistant to degrading due to heat.

A HIGHER, SLOPED SMOKE CHAMBER

- Gradual slope reduces turbulence and evacuates smoke from the firebox more efficiently.
- No smoke spills from the fire chamber.

SMALLER THAN THE FIREBOXES IT WILL BE REPLACING

- No need to cut out existing framing to make room for the Forever Fireplace.

FULLY INSULATED

- A fully insulated firebox results in superior heat radiation.

APPROVED WITH VENTED OR VENT FREE GAS LOGS

- A simple conversion allows for the use of vented or vent free gas logs.

1/2" CLEARANCE TO BACK AND SIDES OF FIREBOX, 0" CLEARANCE TO THE TOP OF STANDOFFS AND BOTTOM OF THE FIREBOX

- Minimal clearances allow for placement in smaller cavities.

LISTED TO UL-127

- The rigorous UL testing and listing requirements assure consistent quality in materials and manufacturing standards.

FEATURES

Venting requirements	8" VENTIS CLASS A
UL-Listing	UL-127
Material	Stainless Steel
Included	Mesh screen

OPTIONS

- Outside air intake
- Glass doors
- Trim kit

FIREPLACE OPENING DIMENSIONS

OCV-RR-36	35.63"(W) x 16.8"(H) x 20.86"(D)
OCV-RR-42	41.63"(W) x 16.8"(H) x 20.86"(D)



copperfield.com